

### SR60 RAIL

#### DESCRIPTION

Designed for exhaust extraction thanks to one or several trolleys sliding on it. Waterproofness between rail and trolley is ensured by rubber lips resisting to high temperatures.

#### CARACTERISTICS

- Aluminium rail, monoblock type, very strong.
- Lengths available in 3,00m or 6,00m
- Rails are extruded with specific shape, designed for fixture of supports and others accessories.
- Rail is composed of:
  - 2 outer slide channels permitting to the trolleys to slide
  - 2 inner slide channels permitting to fix the rubber lips

#### REFERENCE

- |           |            |
|-----------|------------|
| Ref. 6980 | 3.00m rail |
| Ref. 6981 | 6.00m rail |

#### OPTIONAL

- Additional rail length
- Chimney for roof or wall exit
- Trolley
- Adjustable supports
- Balancers with ratchet
- Mechanical reel



#### AVANTAGES

- Working space is free
- Aesthetic
- Light & rust resistant

#### WARRANTY

1 year



Export/TG/2013/10

#### SACATEC EQUIPEMENT

30, Rue de la Malmaison – ZAE de la Grande Couture – 95500 GONESSE – France

Tel. +33 1 39 85 96 05 – Fax +33 1 39 87 56 09 – [www.sacatecequipement.com](http://www.sacatecequipement.com)